

AGROMAGIC AC / DC 4, 6, 8, 10 Station Specification Sheet

- Time based & volume based irrigation
- Loop irrigation (Misting)
- Proportional fertigation
- 4 starts a day
- Master valve by programing (otherwise as irrigation valve)
- Remote manual irrigation ON/Off
- Remote irrigation plan enable disable
- Remote seasonal adjustment 10% 150%
- Low/High flow detection (volume irrigation only)
- Un-planned flow detection (volume irrigation only)
- Auto water close on high flow detection (volume irrigation only)
- Online alerts to cell phone or to e-mail list
- Online reports such as water consumption, alerts by user, communication state
- Online hourly status report: valves state, accumulator, periodic flow rate, battery charge level (DC only)
- Weekly water consumption report by e-mail
- Periodical battery charge level trend
- Excel sheet report export by click

Communication

- 2.5G (or higher) Cellular network GSM 850MHz, EGSM 900MHz, DCS 1800MHz, PCS 1900MHz.
- This product is using radio communication. One must keep at least 25cm from human body in standard working.

Dimensions :

- Width: 6.5", 165mm
- **Height**:4.9", 125mm
- **Depth**: 3.15", 80mm
- Weight: 26.5oz, 750gr

Electrical Specifications:

AC Controller:

- Input voltage: 24VAC | Output voltage for N.C. solenoids: 24VAC
- Dry contact sensor input
 <u>DC Controller</u>
- Input voltage: 12VDC | Output voltage for DC latch solenoids: 13.4VDC
- Dry contact sensor input